

Koamtac KDC 270 - Setup without Offline Scan

Scanner

Koamtac KDC 270

Setting up the scanner on the iPad

To use the scanner with the iPad hardware, please proceed exactly as follows during setup, i.e. do not install any software from the supplied CD and do not make any other settings.

Setup on the scanner

1. Press both arrow keys together to enter the menu.
2. Navigate down to the item "BT Config" and select it with the middle scan button.
3. Select Connect Device and activate the MFi (iPhone) option if it is not already active.
4. Select Save & Exit to save.
5. Scroll down and make the following additional settings, saving each with Save & Exit:
 - Auto Power On: Enabled
 - Wakeup Nulls: Enabled
6. In the previous menu, select the bottom item "Top Menu" to return to the Main Menu.

Setup on the iPad

1. Select Settings -> Bluetooth and activate it.

Setup on the scanner part 2

1. In the submenu "BT Service", select Discovering.

(the discovering process takes about 40 seconds)

1. Select the corresponding iPad and confirm with the middle scan button.
2. Select "Use Default" and confirm again with the middle scan button.

Setup on the iPad part 2

1. A prompt appears on the iPad asking whether to pair the scanner; click Pair here.
2. The scanner is now connected to the iPad and can be used in the DeDeSales software.

Troubleshooting

1. If MFi (iPhone) is missing under Connect Device, it must first be set to Enabled under System Config -> MFi Mode.

Setting up the scanner on Windows device

To use the scanner with the tablet / laptop hardware, please proceed exactly as follows during setup, i.e. do not install any software from the supplied CD and do not perform any other

Setup on the scanner

1. Press both arrow keys together to enter the menu.
2. Navigate down to the item "BT Config" and select it with the middle scan button.
3. Select Connect Device and activate the SPP option if it is not already active.
4. Select Save & Exit to save.
5. Scroll down and make the following additional settings, saving each with Save & Exit:
 - Auto Power On: Enabled
 - Wakeup Nulls: Enabled
6. In the previous menu, select the bottom item "Top Menu" to return to the Main Menu.
7. In the submenu "BT Service", select Pairing.
8. To use the scanner, you must exit the configuration menus.

Setup in the Microsoft Windows operating system

1. Start -> Bluetooth & other devices -> activate Bluetooth.
2. Add Bluetooth or other device -> click Bluetooth.
3. Select the KDC270, wait until it is connected and click "Completed".
4. The scanner is now connected to the Windows device and can be used in the DeDeSales software.

Setting up the scanner on Android device

To use the scanner with the Android hardware, please proceed exactly as follows during setup, i.e. do not install any software from the supplied CD and do not make any other settings.

Setup on the scanner

1. Press both arrow keys together to enter the menu
2. Navigate down to the item "BT Config" and select it with the middle scan button.
3. Select Connect Device and activate the SPP option if it is not already active.
4. Select Save & Exit to save.
5. Scroll down and make the following additional settings, saving each with Save & Exit:
 1. Auto Power On: Enabled
 2. Wakeup Nulls: Enabled
6. In the previous menu, select the bottom item "Top Menu" to return to the Main Menu.

Setup on the Android device

1. Settings -> Connections -> select Bluetooth and set to "On".

Setup on the scanner part 2

1. In the submenu "BT Service", select Discovering.

(the discovering process takes about 40 seconds)

1. Select the corresponding Android device and confirm with the middle scan button.
2. Select "Use Default" and confirm again with the middle scan button.

Setup on the Android device part 2

1. A prompt appears on the Android device asking whether to pair the device. Confirm this with OK.
2. The scanner is now connected to the Android device and can be used in the DeDeSales software.